



OIL-FREE LEADER BUSHINGS

—Special solid lubricant embedded type with head—



OIL-FREE LEADER BUSHINGS

—Straight type with special solid lubricant embedded—



ⓘ Non JIS material definition is listed on P.1351 - 1352

RoHS **GBHEZ**

Usable temperature range for the special solid lubricant: up to 80°C

SUJ2
 Special solid lubricant
 MoS₂ (embedded)
 58HRC~

RoHS **GBSEZ**

Usable temperature range for the special solid lubricant: up to 80°C

SUJ2
 Special solid lubricant
 MoS₂ (embedded)
 58HRC~

dG6	T	Dm5	H	ℓ																				
				L15	L20	L25	L30	L35	L40	L50	L60	L70	L80	L100	L130	L150								
10	5	14	16	15	20	20	20	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
13		20	25	15	20	25	25	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
16	6	25	30	15	20	25	30	35	30	30	—	—	—	—	—	—	—	—	—	—	—	—	—	
20		30	35	—	20	25	30	35	40	40	40	—	—	—	—	—	—	—	—	—	—	—	—	
25	8	35	40	—	—	25	30	35	40	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50
30		42	47	—	—	25	30	35	40	50	60	60	60	60	60	60	60	60	60	60	60	60	60	60
35	10	48	54	—	—	—	—	—	40	50	60	70	70	70	70	70	70	70	70	70	70	70	70	70
40		55	60	—	—	—	—	—	40	50	60	70	80	80	80	80	80	80	80	80	80	80	80	80
50	12	70	75	—	—	—	—	—	—	—	60	70	80	100	100	100	100	100	100	100	100	100	100	100

dG6	t	Dm5	ℓ																				
			L15	L20	L25	L30	L35	L40	L50	L60	L80	L100											
13	6	20	15	20	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
16		25	15	20	25	30	35	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
20		30	15	20	25	30	35	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
25	8	35	—	20	25	30	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
30		42	—	20	25	30	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
35	8	48	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
40		55	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
50		70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Part Number		U/Price 1~9												
Type	d	L15	L20	L25	L30	L35	L40	L50	L60	L70	L80	L100	L130	L150
GBHEZ	10													
	13													
	16													
	20													
	25													
	30													
	35													
	40													
	50													

Part Number		U/Price 1~9										
Type	d	L15	L20	L25	L30	L35	L40	L50	L60	L80	L100	
GBSEZ	13											
	16											
	20											
	25											
	30											
	35											
	40											
	50											

Order **Part Number** — **L**
GBHEZ13 — **40**

Days to Ship **Quotation**

Price **Quotation**

• Oil-free type.....Special solid lubricant eliminates the need for lubrication. (Applying initial running-in oil prior to use can enhance the product's durability furthermore.) Please note that oil oozes out from the solid lubricant at 80°C.

Order **Part Number** — **L**
GBSEZ35 — **60**

Days to Ship **Quotation**

Price **Quotation**

ex Example

■ Stopper for The Straight Leader Bushing

Screw plugs are commonly used as a stopper to hold straight leader bushings. The bushing is provided with a groove on its outer circumference where the screw plug is locked in. Since the screw plug does not directly hold the bushing's thin wall, deflection of its internal diameter can be minimized.

Leader bushing's internal diameter (d)	Applicable screw plugs
13 · 16 · 20	MSW 6
25~50	MSW 8